



## Line Post Porcelain Insulator with Top Clamp (ANSI C29.7)

Solid core porcelain insulators featuring an integral **Top Clamp** for secure vertical or horizontal conductor mounting. Eliminates tie wires and ensures consistent grip. Manufactured to strict **ANSI C29.7** standards.

- **Compliance:**ANSI C29.7
- **Classes:**57-11 to 57-26
- **Mounting:**Integral Top Clamp (Vertical/Horizontal)
- **Cantilever Strength:**12.5 kN (2800 lbs)

### TECHNICAL SPECIFICATIONS (ANSI C29.7)

ANSI CLASS	CREEPAGE (MM)	DRY ARCING (MM)	CANTILEVER (KN)	LOW FREQ FLASHOVER (DRY/WET)	IMPULSE FLASHOVER (POS)	WEIGHT (KG)
57-11	356	165	12.5	70 / 50 kV	120 kV	6.8
57-12	559	241	12.5	100 / 70 kV	160 kV	10.0
57-13	737	311	12.5	125 / 95 kV	200 kV	11.8
57-14	1015	368	12.5	140 / 110 kV	230 kV	15.9
57-15	1145	438	12.5	160 / 130 kV	265 kV	18.6
57-21	356	165	12.5	70 / 50 kV	120 kV	7.5
57-25	1145	438	12.5	160 / 130 kV	265 kV	19.5
57-26	1346	489	12.5	180 / 140 kV	300 kV	--

### DIMENSIONAL DRAWINGS

